



## PRODUCT DATA SHEET

### Oilzum 80W-90 Gear Oil

OILZUM GEAR OILS are multipurpose, extreme pressure gear lubricants which are recommended for hypoid and bevel gear sets used in many front and rear drive differentials. These gear oils are intended for service fill, top-off and refill of hypoid and other drive axles which recommend API GL-5 gear lubricants. Also suitable for use in manual transmissions where a GL-5 gear lubricant is recommended. Meet~ or exceeds API GL-5, API MT-1, MIL-PRF-2105E, PG-2 and Mack GO-J.

#### TYPICAL PROPERTIES

PROPERTY	80W-90
AGMA Number	5EP
ISO Viscosity	220
Viscosity, cSt @ 40°C	160
cSt @ 100°C	15.2
Viscosity Index	95
Gravity, ° API	25.7
Flash Point, °F	415
Pour Point, °F	-15
Oxidation stability (ASTM D 2893)	5.6
Demulsibility (ASTM D2711)	86.3
Total free water, ml	
Emulsion, ml	0.05
Rust Test (ASTM D665)	Pass
Copper strip corrosion (ASTM D130)	1
Foam test (ASTM D 892), foam volume, ml Sequences 1-3	TRIO

Revised 11/15

DENNISON LUBRICANTS, INC .• 111 Rhode Island Avenue. LAKEVILLE MA 02347 • 800.564.5142

All reasonable care has been taken to ensure that the information herein is accurate as of the date of printing. The test results listed are typical properties only. DENNISON LUBRICANTS, INC. strives for continuing improvement in all of our products. Slight formula and blending changes may result in minor color and/or appearance changes.