



Product Data Sheet

Oilzum Diesel Monograde Motor Oils

Oilzum Diesel Monograde motor oils are high performance, straight grade, heavy-duty engine oils that combine selected base stocks with a carefully balanced additive package. **Oilzum Diesel Monograde motor oils** are designed to enhance engine performance and protect engine parts for extended life and reduced maintenance costs.

Oilzum Diesel Monograde motor oils are very resistant to the formation of high temperature deposits. The dispersant package works to keep the cooler areas of the engine from buildup of sludge and other harmful deposits. **Oilzum Diesel Monograde motor oils** exceed the requirements of the following API service categories: SAE 10W (CF/SL), 30 (CF, CF-2, SL), 40 (CF, CF-2, SL) and 50 (CF, CF-2, SL). **Oilzum Diesel Monograde motor oils** meet the requirements of Allison C3/C4.

TYPICAL PROPERTIES	Method	10W	30	40	50
Kinematic Viscosity @40°C, cSt	ASTM D445	42.2	98.2	138.5	189
Kinematic Viscosity @100°C, cSt	ASTM D445	7.0	11.8	14.7	17.5
Viscosity Index	ASTM D2270	125	110	106	100
Density @15°C, lbs/gal	Calculated	7.27	7.36	7.39	7.45
CCS @(n°C), cP Maximum	ASTM D5293	5,000(-25)	N/A	N/A	N/A
Pour Point, °F	ASTM D5949	-32.8	-15	-10	10
Flash Point (COC), °F	ASTM D92	420	450	450	480
TBN	ASTM D974	8.5	8.5	8.5	8.5
Sulfated Ashe, Mass %	ASTM D874	1.0	1.0	1.0	1.0

Oilzum products have exceeded the needs of auto enthusiasts and champion racers since 1905!

Revised 6/15/18

DENNISON LUBRICANTS, INC. ■ 102 CHARLES A. ELDRIDGE DRIVE ■ LAKEVILLE MA 02347 ■ 800.564.5142

All reasonable care has been taken to ensure that the information herein is accurate as of the date of printing. The test results listed are typical properties only. DENNISON LUBRICANTS, INC. strives for continuing improvement in all of our products. Slight formula and blending changes may result in minor color and/or appearance changes.