



## **PRODUCT DATA SHEET**

### **Oilzum Special Syn Blend Motor Oil**

**Oilzum Special Syn Blend** motor oils are formulated in the viscosities that modern automotive manufacturers are recommending for their engines. They are designed to exceed the demanding lubrication requirements of engines equipped with the latest emission controls and turbochargers. These oils, with their synthetic blended base oils and leading edge additive technology, are specially formulated to provide superior protection, resist oxidation and meet the new lower volatility requirements of ILSAC GF-5.

**Oilzum Special Syn Blend** motor oils are API Licensed (#2359) to meet the American Petroleum Institute's (API) highest performance Gasoline Engine Service category SN. These viscosity grades are classified by the American Petroleum Institute (API) as "Resource Conserving" engine lubricants, and ILSAC GF-5.

**Oilzum** products have exceeded the needs of auto enthusiasts and champion racers since 1905!

#### **TYPICAL PROPERTIES**

<b>Property</b>	<b>5W20</b>	<b>5W30</b>	<b>10W30</b>
Viscosity, cSt @ 40°C	50.87	64.00	70.05
Viscosity, cSt @ 100°C	8.73	10.71	10.56
Viscosity Index	150	158	142
Pour Point, °C	-45	-44	-40
Sulfated Ash, Wt (%)	0.92	0.92	0.92
Zinc, wt. %	0.085	0.085	0.085
Phosphorous, wt. %	0.077	0.077	0.077
Calcium, wt. %	0.214	0.214	0.214
Specific Gravity	0.849	0.850	0.856
HTHS	2.73	3.07	3.18
API Service Performance	SN	SN	SN
ILSAC GF-5	Yes	Yes	Yes
Resource Conserving	Yes	Yes	Yes

Revised 1-13-12

DENNISON LUBRICANTS, INC. ■ 102 CHARLES A. ELDRIDGE DRIVE ■ LAKEVILLE MA 02347 ■ 800.564.5142

All reasonable care has been taken to ensure that the information herein is accurate as of the date of printing. The test results listed are typical properties only. DENNISON LUBRICANTS, INC. strives for continuing improvement in all of our products. Slight formula and blending changes may result in minor color and/or appearance changes.