



PRODUCT DATA SHEET

Oilzum Syn-Blend Motor Oil

Oilzum Synthetic Blend Motor Oils are formulated in the viscosities that modern automotive manufacturers are recommending for their engines. They are designed to exceed the demanding lubrication requirements of engines equipped with the latest emission controls and turbochargers. These oils, with their synthetic blended base oils and leading edge additive technology, are specially formulated to provide superior protection, resist oxidation and meet the new lower volatility requirements of ILSAC GF-5.

Oilzum Synthetic Blend Motor Oils are API Licensed (#2359) to meet the American Petroleum Institute's (API) highest performance Gasoline Engine Service category SN Plus. These viscosity grades are classified by the American Petroleum Institute (API) as "Resource Conserving" engine lubricants, and ILSAC GF-5.

Oilzum products have exceeded the needs of auto enthusiasts and champion racers since 1905!

TYPICAL PROPERTIES

Property	5W20	5W30
Viscosity, cSt @ 40°C	50.87	64.00
Viscosity, cSt @ 100°C	8.73	10.71
Viscosity Index	150	158
Pour Point, °C	-45	-44
Sulfated Ash, Wt (%)	0.92	0.92
Zinc, wt. %	0.085	0.085
Phosphorous, wt. %	0.077	0.077
Calcium, wt. %	0.214	0.214
Specific Gravity	0.849	0.850
HTHS	2.73	3.07
API Service Performance	SN Plus	SN Plus
ILSAC GF-5	Yes	Yes
Resource Conserving	Yes	Yes