



CORPORATE HEADQUARTERS

102 Charles A. Eldridge Drive
Lakeville MA 02347

DISTRIBUTION

761-765 Water Street
Gardiner ME 04345

MANUFACTURING

694 Millbury Street
Worcester MA 01606

Voice 800.564.5142 Fax 800.649.0720

Oilzum Synthetic Transmission Oil 50

Oilzum Synthetic Transmission Oil 50 is a SAE 50 transmission lubricant designed specifically for extended drain and severe service in heavy-duty manual transmissions which require a synthetic or conventional non-EP transmission lubricant. The superior all-season lubricating properties mean less friction in the transmission resulting in a potential for improved fuel economy.

Oilzum Synthetic Transmission Oil 50 is formulated from a synthetic base stock with a high viscosity index and low pour point to ensure superior year-round performance. It also contains an anti-wear additive, along with rust, oxidation, and corrosion inhibitors that protect bearings and synchronizer, reduce component wear and promote longer transmission and lubricant life.

Oilzum Synthetic Transmission Oil 50 is a specially formulated synthetic transmission lubricant that meets or exceeds the following performance requirements:

- Eaton Transmission Div., PS-164 Rev. 7(Not Eaton Listed)
- Mack Truck TO-A-Plus
- Navistar TMS 6816
- API MT-1
- ArvinMeritor 0-81
- ZF Freedom Line

Typical Properties	Test Method	Units	Value
API Classification			GL-4
Appearance, visual			Amber
Viscosity @ 40 °C	ASTM D445	cSt	139
Viscosity @ 100 °C	ASTM D445	cSt	18
Viscosity Index	ASTM D2270		144
Brookfield Viscosity, -40°C	ASTM D2983	cP	120,000
Foam Test	ASTM D892		Pass
Pour Point	ASTM D 97	°C	<-45
Flash Point, COC	ASTM D92	°F	437
FZG, Stage, Pass			10 Stage Pass
Copper strip corrosion, (212°F) &(250°F)	ASTM D130		1A, Pass

Oilzum products have exceeded the needs of auto enthusiasts and champion racers since 1905!

Revised 2/28/18