



PRODUCT DATA SHEET

Oilzum TO-4 Type Fluid

Oilzum TO-4 Type Fluid is designed to provide superior wear and oxidation protection in power transmissions and hydraulic systems. This product meets the service requirements of Cat TO-4 and Komatsu Micro Clutch type fluids. It also meets the service requirements of Allison C4 and other transmission fluids where a Cat fluid has been specified.

Over the past two decades, most power transmissions have evolved from motor oil and multi-viscosity recommendations to straight weight TO-4 transmission fluids. Oilzum TO-4 Type fluid provides protection for the frictional elements, both metallic and non metallic, found in today's power transmissions. It also has been noted to eliminate brake noise, prevent slippage, inhibit metal to metal contact and control oxidation to prevent deposit formation.

Typical Properties

Property	10W	30
Viscosity, cSt @ 40°C	37.2	96.8
Viscosity, cSt @ 100°C	6.7	11.4
Viscosity Index	97	96
Pour Point, °C	-35	-28
Flash Point °C	203	220
Specific Gravity	0.8860	0.8980

Revised 1-4-2011

DENNISON LUBRICANTS, INC. ■ 102 CHARLES A. ELDRIDGE DRIVE ■ LAKEVILLE MA 02347 ■ 800.564.5142

All reasonable care has been taken to ensure that the information herein is accurate as of the date of printing. The test results listed are typical properties only. DENNISON LUBRICANTS, INC. strives for continuing improvement in all of our products. Slight formula and blending changes may result in minor color and/or appearance changes.