Product Data Sheet

Oilzum Synthetic dexos1 Gen2 Motor Oils

Oilzum Synthetic dexos1 Gen2 Motor Oils are designed to exceed the demanding lubrication requirements of today's naturally aspirated, turbo-charged and super charged gasoline engines. Specially formulated with 100% synthetic base oils in combination with leading edge additive technology, they deliver exceptional resistance to thermal breakdown, oil thickening and low temperature fluidity. They provide superior protection against wear and deposit formulation under the most severe driving conditions, as well as providing protection against LSPI.

Oilzum Synthetic dexos1 Gen2 Motor Oils are specially formulated to meet the American Petroleum Institute's (API) highest performance Gasoline Engine Service category SN Plus. These viscosity grades are classified by API as "Energy Conserving" engine lubricants, and meet ILSAC GF-5. All viscosity grades are recommended for the requirements of previous categories SM, SF, SG, SH, and SJ.

Oilzum Synthetic dexos1 Gen2 Motor Oils are also formulated to meet the most demanding performance requirements of the new dexos1 Gen2 specification for gasoline-fueled General Motors vehicles.

TYPICAL PROPERTIES	0W-20	5W-30
Viscosity @40°C, cSt	42.76	61.12
Viscosity @100°C, cSt	8.1	10.94
Viscosity Index	166	173
Pour Point, °C	-51	-48
Sulfated Ash, wt. %	0.91	0.83
Zinc, wt. %	0.0822	0.0833
Phosphorus, wt. %	0.0752	0.0756
Calcium, wt. %	0.1348	0.1324
Specific Gravity	0.8454	0.8467
HTHS	2.6	3.19
API Service performance	SN Plus	SN Plus
ILSAC GF-5	Yes	Yes
Energy Conserving	Yes	Yes

Oilzum products have exceeded the needs of auto enthusiasts and champion racers since 1905!

Revised 6/13/18