



Product Data Sheet

Pennwood Syn-Blend Motor Oils

Pennwood Synthetic Blend Motor Oils are premium quality motor oils designed to provide optimum performance in today's high output gasoline engines in passenger cars, vans, SUV's and light trucks. These oils are specifically formulated to provide superior protection, resist oxidation, meet lower volatility requirements, and protect against low speed pre-ignition in engines.

Pennwood Synthetic Blend Motor Oils are API Licensed (#2359) to meet the American Petroleum Institute's (API) highest performance Gasoline Engine Service category SN Plus. These viscosity grades are classified by the American Petroleum Institute (API) as "Resource Conserving" engine lubricants, and ILSAC GF-5.

Property	5W20	5W30
Viscosity, cSt @ 40°C	50.87	64.00
Viscosity, cSt @ 100°C	8.73	10.71
Viscosity Index	150	158
Pour Point, °C	-45	-44
Sulfated Ash, Wt (%)	0.92	0.92
Zinc, wt. %	0.085	0.085
Phosphorous, wt. %	0.077	0.077
Calcium, wt. %	0.214	0.214
Specific Gravity	0.849	0.850
HTHS	2.73	3.07
API Service Performance	SN Plus	SN Plus
ILSAC GF-5	Yes	Yes
Resource Conserving	Yes	Yes

DENNISON LUBRICANTS, INC. ■ 102 CHARLES A. ELDRIDGE DRIVE ■ LAKEVILLE MA 02347 ■ 800.564.5142

All reasonable care has been taken to ensure that the information herein is accurate as of the date of printing. The test results listed are typical properties only. DENNISON LUBRICANTS, INC. strives for continuing improvement in all of our products. Slight formula and blending changes may result in minor color and/or appearance changes.

Revised
10/3/2018