

**CORPORATE HEADQUARTERS**102 Charles A. Eldridge Drive
Lakeville MA 02347**DISTRIBUTION**761-765 Water Street
Gardiner ME 04345**MANUFACTURING**694 Millbury Street
Worcester MA 01606

Voice 800.564.5142 Fax 800.649.0720

Oilzum 190 Cut NC

Oilzum 190 Cut NC is a medium to heavy duty Non Chlorinated cutting oil developed for difficult to machine alloys. **Oilzum 190 Cut NC** is a mixture of traditional metalworking additives, lubricity components, and proprietary performance ingredients blended into a high quality base stock.

Oilzum 190 Cut NC can be used in many machining applications including tapping, thread cutting, form grinding, roll grinding, drilling, and turning. **Oilzum 190 Cut NC** contains no active sulfur so it can also be used on the lube side.

*Masters Machine of Round Pond Maine endorses the use of **Oilzum 190 Cut NC** in both ferrous and non-ferrous metal removal applications.*

Typical Characteristics

Test Description	Test Method	Units	Value
Viscosity @ 40°C	ASTM D445	cSt	38
Chlorine	XRF	ppm	0
Flash, COC	ASTM D92	°C	171163
Specific Gravity	ASTM D5355		.88
Color	ASTM D1500		8

Revised 1-26-18



SERVING NEW ENGLAND WITH QUALITY LUBRICANTS SINCE 1868