



Oilzum Industrial

Water based Metalworking Fluids

***OILZUM WS 5000**

Is a water-soluble, semi-synthetic coolant formulated for general machining of aluminum alloys, cast iron and steel with excellent cleaning ability. **OILZUM WS 5000** provides excellent detergency and re-solubility for reduced grime build up on machines. This coolant also provides excellent anti-corrosion properties, and stable performance characteristics yielding a longer sump life. With normal care, **OILZUM WS 5000** resists rancidity and does not present any abnormal disposal problems.

OILZUM WS 5050

General Purpose Semi-Synthetic Cutting Fluid

OILZUM SOL-MAX 460

Chlorinated Soluble Oil Cutting Fluid

***OILZUM GD 822K**

is a premium quality water miscible synthetic coolant formulated for use in grinding of aluminum, cast iron and steel. **OILZUM GD 822K** is highly recommended where the demand for a dependable low maintenance coolant is a must. **OILZUM GD 822K** is a frequent choice for general grinding operations because of its excellent detergency, anti-corrosion and stable performance characteristics.

OILZUM GD 822K also exhibits excellent tramp oil resistance and anti-foaming ability.

OILZUM COOL-MAX HD 870C

High Lubricity Full Synthetic Cutting/Grinding Fluid

OILZUM COOL-MAX MD 830C

General Purpose Full Synthetic Cutting/Grinding Fluid